



RIG 119

Depth Capacity (TVD): 25,000 ft Rig Loads- 65 loads

Loads may vary with Tubular requirements

MAST

Mast Type	Cantilever Triple	Drill Line Size	1 3/8"
Mast Model	DSII	Number of Lines	12
Static Hook Load (lbs)	750,000	Mast Clear Height (ft)	142

SUBSTRUCTURE

Substructure Type	DSII	Substructure Model	Box on Box
BOP-Sub Clear Height (ft)	23'-3"	Rotary Table Model	ZP-275
Ground to KB Height (ft)	27'	Rotary Table Capacity (lbs)	1,000,000
Setback Capacity (lbs)	565,000	Rotary Table Size	27.5"
Racking Capacity (ft)*	25,000	Walking Capability	200'

* Racking Capacity is calculated w/ 4.5" slim hole pipe

Controls

Controls Type	VFD-AC	VFD Bays	4
Controls MFG.	Omron	Engine Bays	4

Engine/Generator Package (Qty. 3)

Engine MFG	Cummins	Engine Horsepower	1480
Engine Model	QSK-50	Engine Tier Rating	2
Generator MFG	AVK	Generator (KW)	1225
Generator model	DSG		

DRAWWORKS (ELECTRIC- AC)

Drawworks Model	PREP-DMI 1800A	Drawworks Drive	1 X Joilet 1800AC
Single Line Pull (lbs)	79,914	Drive Rating (HP)	1800HP
Rated Power (HP)	1800HP	Auxiliary Brake	Wichita 436
Transmission Model	3 Speed		

OVERHEAD EQUIPMENT

Block Model	McKinney (Becket)	Block Capacity (lbs)	800,000
-------------	-------------------	----------------------	---------

MUDPUMPS (2)

Model	F-1600	Mud pump Drive	1 X 1600 ACMotor
Rated Power (HP)	1600 (hp)	Pump drive rating (HP)	1600
Stroke Length	12"	*** 7500 psi High pressure circulating system	

MUD SYSTEM

Total Volume (bbl)	1240	# of Mudtanks	2
Active Volume (bbl)	1135	# of Compartments	10 Useable
Trip Tank Volume (bbl)	*Contact Marketing	Pill Tank Volume (bbl)	2 X 85
Agitators Power (qty)	9 x (10 HP)	Centrifugal Pump Sizes	Five - 5 x 6 x 11
Shale Shaker	3 x Brandt King Cobra	Gas Buster	48" X 18'



RIG 119

ACCUMULATOR

Accumulator Manufacture	USA Oil Tools	Operating Pressure (psi)	3000
Accumulator Volume (Gal)	240	# of stations	6

BOP'S

Based on operator's program requirements

CHOKE MANIFOLD

Pressure Rating & Size	10000psi x 4"
------------------------	---------------

MISCELLANEOUS EQUIPMENT

Fuel Tank Capacity (Gal)	20,000	Pipetubs	Conventional
# Fuel Tanks	1	Catwalk	Canrig 3000
Water Tank Capacity (bbl)	500	Iron Roughneck	ST-80
# Water Tanks	1		

TUBULARS

Based on operator's program requirements

BOILER

Boiler Manufacture	York-Shipley	Boiler Rating (hp)	(150 HP)
		Water Tank Capacity (bbl)	150

TOPDRIVE

Manufacture	Canrig	Top Drive Capacity (lbs)	1,000,000
Model	1250AC	Max Drill Torque	51,400 ft/lbs
Rated Input Power	1150 HP	Breakout Torque	95,000 ft/lbs
Makeup Torque	71,000 ft/lbs		
Max Speed	265 rpm		